



Main Feature:

- Socket with PCB terminal.
- No reduction of protection class or creepage/clearance with plastic retainer.
- Easy replacement of relays.
- Socket can be used as connector for diagnosis function.
- Sockets and accessories: RoHS compliance (Directive 2002/95/EC).

Socket with PCB-type terminal

Approvals:



E306487

Accessories:

Metal Retainer:



Plastic Retainer:



Technical data:

Rated current	12A
Rated voltage / max. Switching voltage AC	150/300 VAC
Dielectric strength coil-contact circuit	2,500 V _{rms}
Clearance / creepage coil-contact circuit	≥ 4/4mm
Material group of insulation parts	≥ IIIa
Insulation to IEC 60664-1	
Type of insulation coil-contact circuit	reinforced
Open contact circuit	functional
Rated insulation voltage	250V
Pollution degree	2
Rated voltage system	230/400V
Over voltage category	III
RoHS Directive 2002/95/EC	
Sockets, retainers and marking tag:	compliant
Degree of protection DIN 40050	IP20
Ambient temperature range	-25...+70°C
Terminals	PCB
Insertion cycles	A (10)
Max. Insertion Force total	100N
Mounting distance	0, dense packing
Weight	3g
Packaging unit	100pcs.

Order Information:

CSR - P 35

①

②

③

①	Item:	CSR
②	Contact form:	P (for PCB Terminal)
③	Terminal Pitch:	35 (for 3.5mm Terminal Pitch) 50 (for 5.0mm Terminal Pitch)

Dimension:

